



LOADOLL II



Dual Hydraulic Controls

Well protected, illuminated hydraulic controls are located just rear of the axle.



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers



Standard & Optional Equipment / Features Loadoll II

S=Standard O=Optional

MODEL LOADOLL II	
MAIN FRAME	
- 10,000 lb. Distributed Over Full Length of Deck	S
- Rigid Tubular Steel Sub-Frame (Powder Coated Black), Full Length High Quality Polymer Wear Pad (Deck Mounted)	S
- Positive Bed Hold-Down-Frame Mounted with Safety Anti-Lock Tilt Lockout	S
CROSSMEMBERS	
- 2" x 2" Square Tubing 11 Gauge 8" Centers	S
HYDRAULICS	
- PTO Pump, Oil Reservoir	S
- Direct Mounted Pump with Cable Shift PTO and Warning Light	S
- Special Hot Shift PTO / Pump for Auto Transmission	O
DECK AND FEATURES	
- Adjustable Stabilizer Legs	S
- Dual Hydraulic Control Work Stations	S
- Toe Board 3/4" x 2-1/2" Tall Skid Plate 3/4" x 8 Wide	O
- Ratchet Winches for 4" Nylon Strap	O
- 3/16" Smooth Steel Deck	O
- 3/16" Tread Plate	O
LIGHTS	
- FMVSS Light Group with E-Chain Protection System, Dual Lighted Control Stations, Receptacle for Auxiliary Tow Lights, Backup Alarm	S
WINCH	
- 9,000 lb. Worm Gear with Manual Kickout and Spring Tension Plate, 3/8" x 50' Cable	S

MODEL LOADOLL II	
HITCH	
- None	S
- Independent Wheel Lift, Rear Tilt	O
- Independent Wheel Lift, Front and Rear Tilt	O
- Independent Stabilizer Leg, Rear Tilt	O
TIE DOWNS	
- Keyholes; (4) Front; (4) Midship; (4) Rear	S
- (2) Front Mounted 6' Safety T-Hook and Grab Hook, V-Chain Bridle	S
STORAGE AREA / TOOL BOX	
- Chain and Binder Trays at Front of Deck with Sprayed on Rubberized Protection	S
- (2) Chain Storage Trays at Wheel Lift, with (2) 6' Safety Chains with Grab Hook, T-Hook and J-Hook	S
- 30" Steel Tool Box 18" x 18" with Stainless Door	O
- 48" Steel Tool Box 18" x 18" with Stainless Door	O
- 30" Steel Box 18" x 18" with Steel Door	O
- 48" Steel Box 18" x 18" with Steel Door	O
ACCESSORIES	
- Steel Bulkhead, Bed Mounted	S
- Steel Bulkhead, Frame Mounted	O
- Aluminum Bolt-On Bulkhead, Bed Mounted	O
- Rear Work Lights Bulkhead Mounted	O
- Rear Work Lights Bumper Mounted	O
- Magnetic Tow Lights with 30' Coiled Cable	O
FINISH / COLOR	
- Deck and Sub-Frame Powder Coat Black	S

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.



9,000 lb. Winch Standard

The winch may be equipped with optional remote control. The bulkhead is bed mounted with two chain trays.



Hydraulic System

The Loadoll II uses welded hydraulic cylinders with chrome plated rods for long trouble-free service.

Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!

