

# deloupe

## REFUSE SEMI-TRAILER

### GO GREEN WITH DELOUPE

Unique, adaptable, and custom-built: three words that describe Deloupe products to a T. Discover the impressive value of our refuse semi-trailer, which comes with a host of customizable options to meet your specific needs.

#### **AVAILABLE CONFIGURATIONS:**

- Steel
- 3, 4, or 5 axles
- Hallco LIVE FLOORS™
- Hydraulic removable top (flip top), rigid roof, tarp, net, or screen
- Row of horizontal extrusions to reinforce wall
- Lateral opening door
- Choice of colors

For over 38 years now, Deloupe has been designing, manufacturing, and distributing specialized, cutting edge road transportation equipment of the highest quality. Our mission is simple: to meet the specific needs of our customers, while adhering to the highest industry standards.



**AN EXPERT BEHIND YOU**

# deloupe

an expert behind you



To meet your specific needs,  
all other custom options are  
available by request.

For more information,  
contact us:

102 du Parc Industriel  
St-Évariste (Québec) GOM 1S0  
Tel.: 418 459-6443  
Fax : 418 459-6571  
Toll free: 1 888 335-6873  
deloupe@deloupe.com

[www.deloupe.com](http://www.deloupe.com)

## DIMENSIONS

Volume	3,800 cubic feet
Refuse compartment	97" W x 112" H x 53 L
Length	Up to 53 feet Tapered steel monocoque structure
Width	102" overall
Floor	Halco walking floor BRUTE 8000 model
Floor cross member	4" floor I-beam every 12"
Roof cross member (1)	Transversal
Walls	Walls and posts in 1/8" high resistance steel
Upper side members	Rectangular tube (HSS) 6"x 4" x 1/4"

## MECHANICS

Suspension (3)	Triple axle Welded at 72" Capacity: 30,000 lb.
Liftable suspension (1)	Welded at 100" Capacity: 25,000 lb. Antibrake valve included
Fixed-suspension axles (3)	Capacity: 25,000 lb. HN bearing Equipped for steel wheels
Liftable suspension axle (1)	Self-steering capacity: 25,000 lb. HN bearing
Hitching device	Welded kingpin 5 /16" 100,000 psi upper plate
Landing gears	HOLLAND MARK V Capacity: 160,000 lb.

## ACCESSORIES

Pneumatic lift (1)	Included on the 4 <sup>th</sup> axle
Cam protector	Included
Disk rims/ wheels	Steel • Piloted bolts 22.5 x 8.25 Optional: aluminum
Tires	11R22.5 14 ply • Single wheel: 385/65R22.5 20 ply
Hubs and drums (6)	10 bolt piloted hub
Braking system	Sealco Wabco ABS 2S1M
Lighting system	Sealed lights • LED bulbs 3 separate lights on each side
Electrical linkage	7 poles with circuit breakers • ISO3731 socket
Mudflaps with hardware	One pair in black rubber
Rear bumper	Standard: square tube (HSS) 4" x 4" x 3/16" (regulation)
Rear bumper stops (2)	Steel • Welded
Roof	2 section roof covered with plastic netting (flip top)
Ladder (1)	Aluminum, in front with platform

## ESTHETICS

Sanding	Grit blasting
Finishing	Polyurethane
Paint	Polyurethane • Choice of colors