

9016 BT High Dump Cart



Key Features:

Walking tandem design with 20° of travel for smooth transport over uneven terrain.

15" Wide tire tread, centered on 22" rows, allows the cart to maneuver down unlifted rows

Scale system is standard, including a WiFi antenna, allowing the harvester operator to maximize load efficiency.

**Part of the Art's Way
Sugar Beet Harvesting System**
www.artsway-mfg.com

9016-BT High Dump Cart



Additional Features:

Easily converts from LH to RH dump.
Heavy duty pivoting 2" Bull-Pull hitch.
Standard LED rear and side marker lights.
3 position, telescopic tongue.
Rugged, 16R20, 20 ply tires.

Specifications:

Length of box:	16'
Capacity Struck:	930 cu. Ft
Rated Load Capacity	40,000 lbs.
Lip Clearance	7' - 13'
Pivot Height	9' - 15'
Axle Clearance:	20"
Height (low side):	11'
Height (high side):	12'4"
Tread Width	13'2"
Lift Cylinders:	5" & 4" Master Slave
Tilt Cylinders:	4" Parallel
Recommended Min Flow:	15 GPM
Dump Cycle Time @ 15 GMP:	Approx. 90 sec
Dump Cycle Time @ 20 GMP:	Approx. 60 sec

**Part of the Art's Way
Sugar Beet Harvesting System**
www.artsway-mfg.com