



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

	N54-240H	N60-240H	N68-250H	N74-250H
Recommended horsepower (HP PTO)	20 @ 40 *	20 @ 40 *	25 @ 45	25 @ 45
Cutting width (in/mm)	54" 1372	60" 1524	68" 1727	74" 1880
Cutting height (in/mm)	28 ½" 724	28 ½" 724	29 ½" 749	29 ½" 749
Impeller RPM	540	540	540	540
Impeller diameter (in/mm)	24" 610	24" 610	25" 635	25" 635
Impeller depth (in/mm)	7 ½" 191	7 ½" 191	9" 229	9" 229
Number of blades	4	4	4	4
Impeller shaft diameter (in/mm)	1 ¼" 32	1 ¼" 32	1 9/16" 40	1 9/16" 40
Balanced impeller	Std	Std	Std	Std
Drum center height	14" 356	14" 356	14 ½" 368	14 ½" 368
Cylinder for chute deflector (in/mm)	2" X 4" 51 X 102	2" X 4" 51 X 102	2" X 4" 51 X 102	2" X 4" 51 X 102
Chute rotation by hydraulic cylinder (Gear)	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.
Semi Industrial chute (2 deflectors)	Std	Std	Std	Std
Hoses holder	Std	Std	Std	Std
Main auger diameter (in/mm)	17" 432	17" 432	17" 432	17" 432
Balanced auger	Std	Std	Std	Std
Reversible carbon steel cutting edge	Std	Std	Std	Std
Reversible Hardox 450 cutting edge	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel cutting edge	Opt.	Opt.	Opt.	Opt.
Tivar cutting edge	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Driving chain	60	60	60	60
Storage foot	Std	Std	Std	Std
Number of safety bolts	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std
PTO shaft - standard	T20	T20	T40	T40
Adjustable hitch	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1, QH	1, QH	1, QH	1, QH
Approximative weight (lbs/kg) - 1 auger	717 / 325	751 / 341	854 / 387	872 / 396

\* Use with a PTO shaft T40 if more than 30HP  
 The weight includes chute, cylinder for chute deflector, rotation kit and PTO  
 Specifications subject to change without notice