

# 7000 SERIES

85-95 HORSEPOWER

## PERFORMANCE AND POWER AT THE RIGHT PRICE

7000 series utility tractors are as powerful as they are affordable. These value-packed machines are designed to conquer even the toughest tasks, offering a new hydraulic system with best-in-class 5,730 lbs. of 3-point lift capacity. If you're in the market for a utility tractor that provides exceptional performance without any of the costly bells and whistles, look no further than the 7000 series.



## A VALUE-PACKED POWERHOUSE

### ENGINE ›

All 7000 series models come standard with Mahindra's own industry-leading common rail diesel technology (mCRD), offering minimal oil and fuel consumption, high strength steel connecting rods, and a less complex design.

### PTO ›

The economical 540E PTO setting allows for less fuel consumption and lower noise levels in light PTO work. Enjoy robust power for your implements while you avoid breaking the bank.

### TRANSMISSION ›

Standard 15x15 Power Shuttle allows for the widest speed range in class, providing excellent directional control for heavy-duty loader work.

### LIFT CAPACITY ›

With the highest loader lift capacity in its class, 7000 series tractors give you the power you need to work faster and more efficiently.

### COMFORT ›

7000 series tractors come standard with Mahindra's own mComfort Seat—an industry-leading ergonomic seat designed to reduce operator strain during the long workdays.

**Ideal Uses:** Agriculture | Hay | Material Handling | Specialty / Hobby Farming  
Grounds Maintenance / Municipal | Rural Lifestyle | Livestock | Dairy

## KEY ADVANTAGES



### OPTIONAL EQUIPMENT

With a self-leveling valve for loader, as well as a multi-coupler kit to connect all loader hoses at once with a snap, you'll have ultimate versatility for top-tier performance and operational ease.



### LIFT MORE IN THE FRONT

With the highest loader lift capacity in its class, you'll have the strength to carry the heavy loads that the competition can't. Skid steer style quick attach loader bucket comes standard.



### BUILT STOUT FOR HEAVY-DUTY CHORES

These robust machines offer the longest wheelbase in their class, a durable steel frame, and a heavier standard weight to give you the ability to handle larger implements.

# 7000SERIES



## mCOMFORT SUSPENSION SEAT

Every 7000 series model comes standard with Mahindra's own mComfort Seat. Designed and manufactured in the U.S. with industry-leading comfort and support, these seats will keep you comfortable during the long days.



## DELUXE CAB

The 7095 model's deluxe cab is an ergonomic master class, designed specifically for operator comfort during long workdays. Equipped with an ergonomic operator platform, USB charging port, optional buddy seat, air conditioning and heater, and much more, these deluxe cabs will make you forget you ever left your home.



## COMFORTABLE OPERATOR STATION

7000 series tractors come standard with an operator station designed with easy-grip levers and handles, a clear and multifunctional instrument panel, and a lot more, ensuring everything you need is easily within site or reach when you need it.

## 7000 SERIES ATTACHMENTS

TRACTOR	7085 4WD	7095 4WD CAB
LOADER MODEL	7095L	7095CL
Standard Bucket Size [in]		84
Maximum Lift Height [in]		139
Dig Depth [in]		8.75
Lift Capacity to Full Height at Pivot Pin [lbs]		4200
Breakout Force [lbs]		6050
Shipping Weight [lbs]		2100



## 7000 SERIES SPECIFICATIONS

TRACTOR	7085 4WD	7095 4WD CAB
<b>ENGINE</b>		
Type	Four-stroke, Turbocharged, Direct Injection, Water Cooled Diesel Engine	
Engine HP (kW) @ RPM	85 (63.4) @ 2300	95 (70.8) @ 2300
Displacement [in <sup>3</sup> (cc)]	215.4 (3529)	
Number of Cylinders	4	
Bore & Stroke [in]	Bore: 3.78, Stroke: 4.8	
Fuel Tank [gal (L)]	23.7 (89.71)	
<b>DRIVE TRAIN</b>		
Transmission	Full Synchro Mesh with Forward / Reverse Power Shuttle & Constant Mesh Range	
Number of Speeds	15F / 15R	
Clutch	Power Shuttle with Torsional Damper (wet)	
Brakes	Oil Immersed Brakes, Disc Diameter – 8.75", Ball & Ramp Type	
<b>PTO</b>		
Type	2-speed Independent Single Lever PTO	
Rear PTO RPM	540/540E	
Mid PTO RPM	N/A	
PTO HP (kW)	73 (54.4)	83 (61.9)
<b>HYDRAULICS</b>		
Type	Open Center With Position & Draft Control	
Implement Pump Output [gpm (L/min)]	16.17 (61.2)	
Maximum Total Flow [gpm (L/min)]	21.17 (80.1)	
3-Point Hitch	CAT II w/ Telescoping Stabilizers & Flex Links	
Lift Capacity [lb (kg)]	5730 (2594)	
<b>ELECTRICAL</b>		
Battery	12 V, 1000 CCA	
Alternator	12 V, 55 A	12 V, 140 A
<b>DIMENSIONS</b>		
Overall Length [in (mm)]	167 (4241)	
Overall Width [in (mm)]	80.7 (2049)	
Overall Height [in (mm)]	105 (2667)	115 (2921)
Wheelbase [in (mm)]	94.5 (2400)	
Minimum Ground Clearance [in (mm)]	14.1 (358)	
Turning Radius [ft (m)]	13 (4)	
Weight [lb (kg)]	7450 (3379)	8380 (3801)
<b>WHEELS &amp; TIRES</b>		
AG [Front/Rear]	12.4 x 24 / 18.4 x 30 Bias	12.4 x 24 / 18.4 x 30 Radial