

**2600 SERIES** › 2638 HST | 2638 HST CAB | 2645 SHUTTLE | 2645 SHUTTLE CAB  
2660 HST | 2660 HST CAB | 2660 PST | 2660 PST CAB | 2670 PST CAB

# 2600 SERIES

37.4-70 HORSEPOWER

## TAKING COMFORT AND PERFORMANCE TO THE NEXT LEVEL.

The 2600 series offers the most user-friendly compact utility tractors in Mahindra's arsenal. But don't be fooled into thinking these affordable tractors compromise on quality and power. 2600 machines are perfect for general farming and landscaping jobs that require the best of the essentials, while also possessing choice features designed for comfort and convenience. That's a lot of tractor for your dollar.



## CAPABILITY, CONVENIENCE, AND QUALITY

### mCRD™ ENGINE ›

With up to 45% larger engine displacement than the competition, you'll have the power and durability to maximize your potential while reducing emissions.

### TRANSMISSION ›

Whatever your transmission preference, the 2600 series gives you what you want. Choose between either 12F/12R synch shuttle, power shuttle PST, or 3-range HST (depending on model).

### EASILY SERVICEABLE ›

Servicing your tractor has never been easier. Hood and side panels open quickly and efficiently with no tools required, providing ease of access for radiator, battery, filter replacement, and oil checks.

### DELUXE CAB ›

2600 series cabs are specially designed for your comfort and pleasure. The spacious cabs come equipped with standard heater and air conditioning, front window wipers (optional rear wipers), Bluetooth radio, USB port, and 12V socket.

### COMFORT ›

2600 series tractors contain the flattest operator station in their class, with a full rubber mat, allowing for easy entry and filtered vibration. The mComfort™ seat and flat-deck operator platform also ensure complete ergonomic support.



**Ideal Uses:** Specialty / Hobby Farming | Grounds Maintenance / Municipal | Hay Equine / Livestock / Dairy | Rural Lifestyle | Materials Handling | Home

## KEY ADVANTAGES



**LARGEST DISPLACEMENT ENGINE**  
2600 series tractors come equipped with the largest engine displacement in its class, allowing for lower operating RPM, longer life, quieter operations, more hauling capability, and better fuel economy.



**EASE OF ENTRY**  
These tractors possess the flattest operator station in their class, set with a full rubber mat. These features allow for easy entry into the vehicle's station, while also filtering rough vibration to help prevent operator fatigue.



**CONVENIENCE ALL DAY LONG**  
All 2600 series tractors come equipped with fender mounted loader joystick controls, cup holder, 12V socket, and integrated cellphone holder with charger.

# 2600 SERIES



## DELUXE CAB

An optional deluxe cab comes standard with heater and air conditioning, wide opening doors, front window wiper, Bluetooth radio, USB port, and a spacious, comfortable interior.



## TRANSMISSION CHOICES

12 forward and reverse speeds with partial synchromesh (2645), power shuttle (2660 & 2670), or 3-range HST (2638 & 2660). Whatever your transmission preference, there is a 2600 series tractor for you.



## WORK IN COMFORT

All 2600 series tractors come standard with Mahindra's own mComfort seat. Features include extra cushioning for operator relief, mechanical suspension seats, and foldable armrests.

## 2600 SERIES ATTACHMENTS

TRACTOR	2638 HST	2638 HST CAB	2645 SHUTTLE	2645 SHUTTLE CAB	2660 HST	2660 HST CAB	2660 PST	2660 PST CAB	2670 PST CAB
<b>LOADER MODEL</b>	<b>2638L</b>	<b>2638CL</b>	<b>2645L</b>	<b>2645CL</b>	<b>2660L</b>	<b>2660CL</b>	<b>2660L</b>	<b>2660CL</b>	<b>2670CL</b>
Standard Bucket Size [in]	66		66				72		78
Maximum Lift Height [in]	101.4		101.9				115.4		115.4
Dig Depth [in]	4.5		4.8				5.2		5.2
Lift Capacity to Full Height at Pivot Pin [lbs]	1634		2041				3122		3122
Breakout Force [lbs]	2696		3430				5225		5225
Shipping Weight [lbs]	985		1177				1270		1318
<b>BACKHOE MODEL</b>		<b>60B</b>					<b>65B</b>		
Standard Bucket Size [in]		16					18		
Maximum Dig Depth [in]		95					112		
Dig Depth 2' Flat Bottom [in]		93.5					110		
Dig Force Bucket [lbs]		3439					3895		
Dig Force Dipper [lbs]		2214					2358		
Shipping Weight [lbs]		1250					1100		



## 2600 SERIES SPECIFICATIONS

TRACTOR	2638 HST	2638 HST CAB	2645 SHUTTLE	2645 SHUTTLE CAB	2660 HST	2660 HST CAB	2660 PST	2660 PST CAB	2670 PST CAB
<b>ENGINE</b>									
Type	Four-stroke, Naturally Aspirated, Direct Injection, Water Cooled Diesel Engine				Four-stroke, Turbocharged, Direct Injection, Water Cooled Diesel Engine				
Engine HP (kW) @ RPM	37.4 (27.5) @ 2400		44 (33) @ 2600		60 (44.5) @ 2300			70 (52) @ 2300	
Displacement [in <sup>3</sup> (cc)]	166.7 (2732)				161.7 (2650)				
Number of Cylinders	4				3				
Fuel Tank [gal (L)]	9 (34)				16 (60.6)			18.5 (70)	
<b>DRIVE TRAIN</b>									
Transmission	HST - 3 Ranges		Sync, shuttle with part synchromesh		HST - 3 Ranges			Power Shuttle	
Number of Speeds	Infinite		12F / 12R		Infinite			12F / 12R	
Clutch	Damper		Dry, single plate		Damper			Dry Single Plate	
Brakes	Wet Disc Brake, Mechanical								
<b>PTO</b>									
Type	Independent								
Rear PTO RPM	540 @ 2400		540 @ 2650		540 @ 2300				
Mid PTO RPM	2000 @ 2500 (OPT)		N/A		2000 @ 2500 (OPT)			N/A	
PTO HP (kW)	31 (23.2)	29.5 (22)	36 (26.8)		46.3 (34.5)		48.5 (36.2)		53.8 (40.1)
<b>HYDRAULICS</b>									
Type	Open Center								
Implement Pump Output [gpm (L/min)]	7.6 (28.7)		8.2 (31.0)		11.8 (44.7)				
Maximum Total Flow [gpm (L/min)]	11.7 (44.3)		12.7 (48.1)		16.7 (63.2)				
Standard Rear Valve	N/A				1 Spool				
3-Point Hitch	CAT 1				CAT I with Telescoping Stabilizers & Flex Links			CAT II with Telescoping Stabilizers & Flex Links	
Lift Capacity [lb (kg)]	2646 (1200)				3314 (1503)			3528 (1600)	
<b>ELECTRICAL</b>									
Battery	12 V, 800 CCA				12 V, 925 CCA				
Alternator	12 V, 90 A								
<b>DIMENSIONS</b>									
Overall Length [in (mm)]	119.3 (3030)				138.8 (3525)			144.4 (3667)	
Overall Width [in (mm)]	63.2 (1605)				71.1 (1805)			71.5 (1817)	
Overall Height [in (mm)]	94.4 (2400)				102 (2590)				
Wheelbase [in (mm)]	67.7 (1719)				73.7 (1871)			83 (2100)	
Minimum Ground Clearance [in (mm)]	14.5 (370)				15.7 (400)				
Turning Radius [ft (m)]	N/A								
Weight [lb (kg)]	3130 (1420)	3351 (1520)	3285 (1490)	3506 (1590)	4145 (1884)	4585 (2080)	4145 (1884)	4585 (2080)	5390 (2445)
<b>WHEELS &amp; TIRES</b>									
AG [Front/Rear]	7-16 6PR / 11.2-24 4PR		8.3 x 16 / 12.4 x 24		9.5x16 6PR / 14.9x24 6PR			9.5 x 20 / 14.9 x 28	
IND [Front/Rear]	10-16.5 / 43 x 16-20				12x16.5 6PR / 16.9x24 8PR			10.5/80 x 18 / 18.4 x 24	
TURF [Front/Rear]	N/A				LSW305-521 / LSW570-648				