



400 Series Scraper Specifications

A LANDOLL® Company

Product Attributes	414	418
Approximate Weight	20,500 lbs. (9,299 kg)	23,200 lbs. (10,523 kg)
Working Width	10 ft. 0 in. (3.0 m)	11 ft. 0 in. (3.4 m)
Capacity - Heaped	14 yards (10.7 m ³)	18 yards (13.8 m ³)
Capacity - Struck	11.2 yards (8.6 m ³)	16.1 yards (12.3 m ³)
Transport Width	10 ft. 11. in. (3.3 m)	11 ft. 11 in. (3.6 m)
Transport Height	8 ft. 10 in. (2.7 m)	8 ft. 10 in. (2.7 m)
Height With Bowl on Ground	7 ft. 4 in. (2.2 m)	7 ft. 4 in. (2.2 m)
Transport Clearance	18 in. (457 mm)	18 in. (457 mm)
Overall Length	27 ft. 6 in. (8.4 m)	27 ft. 6 in. (8.4 m)
Cutting Edge	CAT, Replaceable	CAT, Replaceable
Style	Roll Out Eject -- Rear Lowering	Roll Out Eject -- Rear Lowering
Hitch	Cast 360° Swivel	Cast 360° Swivel
Tire Size	(2) 26.5 x 25	(4) 20.5 x 25
Wheel Hubs	20-Bolt, 48,500 lbs. (22,000 kg)	10-Bolt, 25,000 lbs. (11,340 kg)
Depth Gauge	Standard	Standard
Complete Factory Assembly	Standard	Standard
Safety Warning Lights & SMV Emblem	Standard	Standard
Safety Chain Kit	Standard	Standard
Auxiliary Draw Bar	Optional	Optional
Tandem Package	Optional	Optional
Hydraulic Disc Brakes	Optional	Optional