

# 9600 "Crop Pro" Spreader

**Large Capacity Industrial Series**



**Compost \* Dry Feed Lot \* Pen Packed \* Sludge Products  
Poultry Litter \* Separator Solids \* Digester Solids \* More**

**Farm Equipment Buyers Trust The Name Meyer!**





**Crop  
Pro**

**"Spread Pattern"**

The New Meyer **Crop Pro** is built for a wide range of spreadable products.

The All New **FPX1** Beater Attachment is second to none in spreading performance. Giving you a Even and consistent Spread All the way across the pattern!



### New "Crop Pro"

- Gate Indicator for Easy Operator Knowledge
- High Lift Guillotine Gate for Precise Material Control
- Large Front Viewing Window for Operator Visibility
- FPX1 Spinner Shock Load Couplers
- Independent Spinner Gearbox Drive to Prevent Contamination
- FPX1 Hydraulic Service Door for Easy Maintenance
- Hydraulic Gear Drive Apron with Variable Speed
- Triple D667XH Floor Chains with Apron
- Enhanced Spread Performance (Wide Pattern)

# ... Is Everything"



## Hydraulic Suspension

- Smooth Ride
- Great Operator Control
- Floatation
- Even Weight Distribution
- Less Operator Fatigue
- Greater Stability

## Pro" Features

- Knowledge
- Metering
- Operator Awareness
- Extend Spinner and Gearbox Life
- System Eliminates Cross
- Easy Operator Servicing
- Variable Speed Control
- Forward Reversing Feature Standard
- (Lengths from 45' to 70')



# 9600 "Crop Pro"

Specifications \* Options

MODEL:	9620 Pull Type	9624 Pull Type	9630 Pull Type
Box Inside Length	20'	24'	30'
Overall Length	32' 5" w/HSTS24	36' 5" w/HSTS30	42'5" w/HSTS45
Inside Width	90 3/4"	90 3/4"	90 3/4"
Overall Width Box/Box w/Std Tires	111"/125.5"	111"/125.5"	111"/125.5"
Inside Height	47.5"	47.5"	47.5"
Overall Height w/FPX1	151.4" w/HSTS24 w/710/50XR26.5	155.2 w/HSTS30 w/710/50R26.5	1152.5" w/HSTS45 w/710/50R26.5
Loading Height	119" w/Trailer	119" w/Trailer	119" w/Trailer
Capacity-Struck/Heaped	600/755 Cu. Ft.	720/925 Cu. Ft	900/1,180 Cu. Ft.
Weight (Approx.) w/FPX1 & Std Tires	17,340#	19,760#	26,320#
Horse Power Required-Min.	200 HP	220 HP	250 HP
Apron Chains	D667XH/3-Aprons	D667XH/3-Aprons	D667XH/3-Aprons
Slats Per Apron	35/105 Per Box	41/123 Per Box	50/150 Per Box
Apron Drive	Hydraulic - Variable	Hydraulic - Variable	Hydraulic - Variable
Reversing Apron	Standard	Standard	Standard
Floor	Super Slide - Solid Poly	Super Slide - Solid Poly	Super Slide - Solid Poly
Box Sides	Steel - 10 gauge	Steel - 10 gauge	Steel - 10 gauge
Front 36" Folding Guard/Deflector	Standard	Standard	Standard
Transport Lights w/Cord	Standard	Standard	Standard
<b>OPTIONS</b>			
Rear Attach FPX1	Optional	Optional	Optional
Silage Extension Package	Optional 36"	Optional 36"	Optional 36"
Scale Packages	Optional	Optional	Optional
Poly Apron Return Liner	Optional	Optional	Optional
<b>TRAILERS (pull type)</b>	<b>*For 9620* HSTS24</b>	<b>*For 9624* HSTS30</b>	<b>*For 9630* HSTS45</b>
Frame	4x8 tubing	4x8 tubing	4x8 tubing
Capacity (Trailer/Spreader/Load)	48,000#	48,000#	90,000#
Axle Configuration	Tandem - Non Steer 25,000# x 2 <b>Fixed Hydraulic Suspension</b>	Tandem Non Steer 25,000# x 2 <b>Sliding Hydraulic Suspension</b>	Tridem - Steerable F&R 33,000# x 3 <b>Fixed Hydraulic Suspension</b>
Heavy Duty Hubs	Grease Filled - 10 Bolt	Grease Filled - 10 Bolt	Grease Filled - 10 Bolt
Articulating Implement Hitch	Std - Requires 1.5" or 2" pin Hammerstrap Style Hitch	Std - Requires 1.5" or 2" pin Hammerstrap Style Hitch	Std - Requires 1.5" or 2" pin Hammerstrap Style Hitch
Poly Fender Liner	Standard	Standard	Standard
Steel Fender Flares	Optional	Optional	Optional
Tire Options:	w/710/50XR26.5 High Floatation 800/45Rx26.5 High Floatation	w/710/50XR26.5 High Floatation 800/45Rx26.5 High Floatation	w/710/50XR26.5 High Floatation 800/45Rx26.5 High Floatation
Brakes (Hyd Hand or Foot Pedal)	Optional	Optional	Standard
Safety Chain/SMV	Optional	Optional	Optional
Tracks in Lieu of Tires	Call	Call	Call

**Farm Equipment Buyers Trust The Name Meyer!**

**Meyer Mfg Corp. \* Dorchester, Wisconsin 54425 \* 715-654-5132**

**1-800-325-9103**

**Email: sales@meyermfg.com \* home page www.meyermfg.com**

