



# Agricultural Seeder Specifications

## Small Ag Series (4 ft. to 6 ft.)

| Product Attributes                            | SSBP-4   | SSBP-5   | SSBP-6   | SSBS-6   |
|---|--|--|--|--|
| Approximate Weight                            | 888 lbs. (403 kg)                                | 1,061 lbs. (481 kg)                              | 1,205 lbs. (547 kg)                              | 1,401 lbs. (636 kg)                              |
| Working Width                                 | 4 ft. 0 in. (1.2 m)                              | 5 ft. 0 in. (1.25 m)                             | 6 ft. 0 in. (1.8 m)                              | 6 ft. 0 in. (1.8 m)                              |
| Transport Width                               | 5 ft. 0 in. (1.25 m)                             | 6 ft. 0 in. (1.8 m)                              | 7 ft. 0 in. (2.1 m)                              | 7 ft. 0 in. (2.1 m)                              |
| Transport Height                              | Dependent Upon Tractor                           | Dependent Upon Tractor                           | Dependent Upon Tractor                           | Dependent Upon Tractor                           |
| Overall Height                                | 4 ft. 5 in. (1.4 m)                              | 4 ft. 5 in. (1.4 m)                              | 4 ft. 5 in. (1.4 m)                              | 4 ft. 5 in. (1.4 m)                              |
| Overall Length                                | 2 ft. 6 in. (0.8 m)                              | 2 ft. 6 in. (0.8 m)                              | 2 ft. 6 in. (0.8 m)                              | 2 ft. 6 in. (0.8 m)                              |
| Seed Box                                      | All Steel Construction with Cover                | All Steel Construction with Cover                | All Steel Construction with Cover                | All Steel Construction with Cover                |
| Seed Box Capacity - Meter Box                 | 1.75 bu.   | 2.187 bu.  | 2.625 bu.  | 2.625 bu.  |
| Seed Box Capacity - Agitator Box              | 1.75 bu.   | 2.187 bu.  | 2.625 bu.  | 2.625 bu.  |
| Seed Meters                                   | Micro-Meter / Blade Agitator                     | Micro-Meter / Blade Agitator                     | Micro-Meter / Blade Agitator                     | Micro-Meter / Blade Agitator                     |
| Seed Meter Drive                              | Ground Driven                                    | Ground Driven                                    | Ground Driven                                    | Ground Driven                                    |
| Seed Meter/Opening Space                      | 8 in. (203 mm) / 4 in. (102 mm)                  | 8.5 in. (216 mm) / 4.25 in. (108 mm)             | 6 in. (152 mm) / 4 in. (102 mm)                  | 6 in. (152 mm) / 4 in. (102 mm)                  |
| Seed Delivery                                 | Broadcast with Wind Deflector Tray               | Broadcast with Wind Deflector Tray               | Broadcast with Wind Deflector Tray               | Broadcast with Wind Deflector Tray               |
| Pulverizer Roller - Front                     | 11.5 in. (292 mm) Cast Iron                      | 11.5 in. (292 mm) Cast Iron                      | 11.5 in. (292 mm) Cast Iron                      | 11.5 in. (292 mm) Cast Iron                      |
| Pulverizer Roller - Rear                      | 9.5 in. (241 mm) Cast Iron                       | 9.5 in. (241 mm) Cast Iron                       | 9.5 in. (241 mm) Cast Iron                       | 9.5 in. (241 mm) Cast Iron                       |
| Pulverizer Axle Bearings                      | Greaseable                                       | Greaseable                                       | Greaseable                                       | Greaseable                                       |
| Pulverizer Axle Size - Front                  | 8.625 in. (219 mm)                               | 8.625 in. (219 mm)                               | 8.625 in. (219 mm)                               | 8.625 in. (219 mm)                               |
| Pulverizer Axle Size - Rear                   | 1.75 in. (44.5 mm)                               | 1.75 in. (44.5 mm)                               | 1.75 in. (44.5 mm)                               | 1.75 in. (44.5 mm)                               |
| Coil Tine Track Remover                       | Standard   | Standard   | Standard   | Standard   |
| Hitch Type                                    | Three-Point Hitch                                | Three-Point Hitch                                | Three-Point Hitch                                | Skid Steer Quick Attach Plate; Three-Point Hitch |
| Hitch Category                                | Cat. I, II Free Link; Cat. I Quick Coupler Hitch | Cat. I, II Free Link; Cat. I Quick Coupler Hitch | Cat. I, II Free Link; Cat. I Quick Coupler Hitch | Cat. I, II Free Link; Cat. I Quick Coupler Hitch |
| Cat. II Quick Coupler Hitch Adaptor Kit       | Optional   | Optional   | Optional   | Optional   |
| Spike Roller - Front (6 ft.)                  | N/A  | N/A  | Optional   | Optional   |
| Notched Rear Roller w/Sprockets               | Optional   | Optional   | Optional   | Optional   |
| Notched Rear Heavy Roller w/Sprockets (6 ft.) | N/A  | N/A  | Optional   | Optional   |
| 5-Strip Brush Agitator Kit for Brome Box      | Optional   | Optional   | Optional   | Optional   |
| 8-Row Brush Agitator Kit for Brome Box        | Optional   | Optional   | Optional   | Optional   |
| Electronic Acre Meter Kit                     | Optional   | Optional   | Optional   | Optional   |
| Lift Sling Kit                                | Optional   | Optional   | Optional   | Optional   |
| Speed Up Kit (Doubles Output)                 | Optional   | Optional   | Optional   | Optional   |
| SMV Emblem                                    | Standard   | Standard   | Standard   | Standard   |
| Powder Coat Paint, Red                        | Standard   | Standard   | Standard   | Standard   |
| Horsepower Requirements                       | 35 HP (26.88 kW) and up                          | 35 HP (26.88 kW) and up                          | 35 HP (26.88 kW) and up                          | 35 HP (26.88 kW) and up                          |
| Recommended Operating Speed                   | 3 to 5 MPH (5 to 8.3 km/h)                       | 3 to 5 MPH (5 to 8.3 km/h)                       | 3 to 5 MPH (5 to 8.3 km/h)                       | 3 to 5 MPH (5 to 8.3 km/h)                       |