



# Chisel Plow Specifications

## 2-Bar Mounted Models

Product Attributes	CPPR2-5	CPPS21-5	CPPR2-7	CPPS21-7
Approximate Weight	455 lbs. (206 kg)	590 lbs. (268 kg)	533 lbs. (242 kg)	722 lbs. (328 kg)
Working Width	5 ft. 0 in. (1.5 m)	5 ft. 0 in. (1.5 m)	7 ft. 0 in. (2.1 m)	7 ft. 0 in. (2.1 m)
Transport Width	6 ft. 6 in. (2.0 m)	6 ft. 6 in. (2.0 m)	8 ft. 6 in. (2.6 m)	8 ft. 6 in. (2.6 m)
Transport Height	4 ft. 0 in. (1.2 m)	4 ft. 0 in. (1.2 m)	4 ft. 0 in. (1.2 m)	4 ft. 0 in. (1.2 m)
Overall Length	5 ft. 3 in. (1.6 m)	5 ft. 3 in. (1.6 m)	5 ft. 3 in. (1.6 m)	5 ft. 3 in. (1.6 m)
Number of Shanks	5	5	7	7
Shank Mount	Rigid	Dual Nested Spring	Rigid	Dual Nested Spring
Shank Size	1 in. x 2 in. x 26 in. (25.4 x 50.8 x 660 mm)	1 in. x 2 in. x 26 in. (25.4 x 50.8 x 660 mm)	1 in. x 2 in. x 26 in. (25.4 x 50.8 x 660 mm)	1 in. x 2 in. x 26 in. (25.4 x 50.8 x 660 mm)
Shank Spacing	12 in. (300 mm)	12 in. (300 mm)	12 in. (300 mm)	12 in. (300 mm)
Shank Working Depth	Maximum 12 in. (300 mm)	Maximum 12 in. (300 mm)	Maximum 12 in. (300 mm)	Maximum 12 in. (300 mm)
Spring Pressure / Trip Resistance	N/A - Rigid Shanks on this Model	550 lbs. to 825 lbs. (248 kg to 371 kg)	550 lbs. to 825 lbs. (248 kg to 371 kg)	N/A - Rigid Shanks on this Model
Shank Trip Height	N/A	5.5 in. (138 mm)	N/A	5.5 in. (138 mm)
Chisel Points Available	2 in. (50.8 mm) Reversible Point or 3 in. (76.2 mm) Reversible Twisted Point	2 in. (50.8 mm) Reversible Point or 3 in. (76.2 mm) Reversible Twisted Point	2 in. (50.8 mm) Reversible Point or 3 in. (76.2 mm) Reversible Twisted Point	2 in. (50.8 mm) Reversible Point or 3 in. (76.2 mm) Reversible Twisted Point
Under Frame Clearance	27.5 in. (688 mm)	27.5 in. (688 mm)	27.5 in. (688 mm)	27.5 in. (688 mm)
Frame Structure	4 in. x 4 in. x .187 in. (100 x 100 x 4.67 mm)	4 in. x 4 in. x .187 in. (100 x 100 x 4.67 mm)	4 in. x 4 in. x .187 in. (100 x 100 x 4.67 mm)	4 in. x 4 in. x .187 in. (100 x 100 x 4.67 mm)
Three-Point Hitch	Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch
SMV Emblem	Standard	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard	Standard
Optional Equipment	Safety Warning Lights Manual Adjust Gauge Wheel Kit Shank and Clamp Assemblies	Safety Warning Lights Manual Adjust Gauge Wheel Kit Shank and Clamp Assemblies	Safety Warning Lights Manual Adjust Gauge Wheel Kit Shank and Clamp Assemblies	Safety Warning Lights Manual Adjust Gauge Wheel Kit Shank and Clamp Assemblies
Horsepower Requirements	10 to 15 HP (8 to 11 kW) per Shank	10 to 15 HP (8 to 11 kW) per Shank	10 to 15 HP (8 to 11 kW) per Shank	10 to 15 HP (8 to 11 kW) per Shank
Recommended Operating Speed	4 to 6 MPH (6.43 to 9.65 km/h)	4 to 6 MPH (6.43 to 9.65 km/h)	4 to 6 MPH (6.43 to 9.65 km/h)	4 to 6 MPH (6.43 to 9.65 km/h)