

| <b>FATBOY MODEL - "10 SERIES"</b>                  | <b>1026RT RR / RS</b> | <b>1030RT SRS / RRS</b> | <b>1036RT SRRS</b>   |
|--|-----------------------|-------------------------|----------------------|
| <b>DIMENSIONS</b>                                  |                       |                         |                      |
| INSIDE LENGTH                                      | 26'                   | 30'                     | 36' 8"               |
| INSIDE WIDTH                                       | 9' 7"                 | 9' 7"                   | 9' 7"                |
| INSIDE HEIGHT                                      | 7' 2"                 | 7' 2"                   | 7' 2"                |
| OVERALL LENGTH                                     | 35' 8"                | 39' 8"                  | 46' 4"               |
| OVERALL WIDTH                                      | 11'                   | 11'                     | 11'                  |
| OVERALL HEIGHT                                     | 13' 6"                | 13' 6"                  | 13' 6"               |
| <b>SPECIFICATIONS</b>                              |                       |                         |                      |
| MAX NET LOAD (OFF ROAD RATING) @ 25 MPH            |                       |                         |                      |
| CAPACITY, STRUCK                                   | 1791 FT <sup>3</sup>  | 2066 FT <sup>3</sup>    | 2524 FT <sup>3</sup> |
| APRON CHAIN  | 667XH PINTLE, 2 SETS  | 667XH PINTLE, 2 SETS    | 667XH PINTLE, 2 SETS |
| REAR DRIVE SHAFT                                   | 2-3/8"                | 2-3/8"                  | 2-3/8"               |
| POWER SOURCE / DIRECT GEARDRIVE                    | HYD - DUAL            | HYD - DUAL              | HYD - DUAL           |
| UPRIGHT SPACING                                    | 16"                   | 16"                     | 16"                  |
| UPRIGHT DESIGN                                     | 2 ½" X 2 ½" TUBE      | 2 ½" X 2 ½" TUBE        | 2 ½" X 2 ½" TUBE     |
| CROSS MEMBER CONSTRUCTION                          | FORMED 5/16" CHANNEL  | FORMED 5/16" CHANNEL    | FORMED 5/16" CHANNEL |
| UNLOADING TIME - (DEPENDENT OF HYD. SYSTEM)        | 35 Seconds            | 45 Seconds              | 55 Seconds           |
| EMPTY WEIGHT                                       |                       | 25,400 LBS              | 31,000 LBS           |
| <b>FEATURES</b>                                    |                       |                         |                      |
| ALL STEEL WELDED FRAME                             | STD                   | STD                     | STD                  |
| CLAD-TUFF FIBERGLASS WOVEN                         | STD                   | STD                     | STD                  |
| SIDE & FRONT PANELS                                | STD                   | STD                     | STD                  |
| SOLID, HIGH MOLECULAR POLY FLOOR                   | STD                   | STD                     | STD                  |
| TIRE SIZE  | 710/50R26.5           | 800/45R26.5             | 800/45R26.5          |
| INTEGRATED BRAKES - HYDRAULIC                      | STD                   | STD                     | STD                  |
| HYDRAULIC SUSPENSION W/RIDE HEIGHT ADJ             | STD                   | STD                     | STD                  |
| DUAL HYDRAULIC GEAR DRIVE                          | STD                   | STD                     | STD                  |
| HYDRAULIC HI-LIFT TAILGATE                         | STD                   | STD                     | STD                  |
| 29" HYD. FRONT FOLD-DOWN                           | STD                   | STD                     | STD                  |
| ARTICULATING AG HITCH / BULL PULL                  | STD                   | STD                     | STD                  |
| DOUBLE VIEWING WINDOW                              | STD                   | STD                     | STD                  |
| LED REAR TURN SIGNAL LIGHTS                        | STD                   | STD                     | STD                  |
| LED MARKER / CLEARANCE LIGHTS / DOT TAPE           | STD                   | STD                     | STD                  |
| PERSONALIZED FARM NAME ON SIDES                    | STD                   | STD                     | STD                  |
| NO ROOF  | STD                   | STD                     | STD                  |
| <b>OPTIONS</b>                                     |                       |                         |                      |
| OPTIONAL TIRE SIZE                                 | 800/45R26.5           | NA                      | NA                   |
| FRONT LIFT AXLE                                    | OPT*                  | OPT                     | OPT                  |
| SIDE-MTD. LED TURN SIGNALS IN ADDITION TO STANDARD | OPT                   | OPT                     | OPT                  |
| BLACK FRAME PAINT                                  | STD                   | STD                     | STD                  |
| STEEL FENDERS W/REAR FLAPS                         | STD                   | STD                     | STD                  |
| SCALES   | NA                    | NA                      | NA                   |