

# COMPACT & UTILITY TRACTOR LOADERS

235TLA | 240TLA | 250TLA | 110TL | 250TL | 615TL | 625TL



# COMPACT & UTILITY TRACTOR LOADERS

## LOADER COMPATIBILITY

| LOADER SERIES | TRACTOR MODEL          |
|---------------|------------------------|
| 235TLA        | BOOMER™ 20, BOOMER™ 25 |
| 240TLA        | BOOMER™ 30, BOOMER™ 35 |
| 250TLA        | BOOMER™ 40, BOOMER™ 50 |

| LOADER SERIES | TRACTOR MODEL |
|---------------|---------------|
| 110TL         | T1510, T1520  |
| 250TL         | T1530         |

| LOADER SERIES | TRACTOR MODEL                                   |
|---------------|---|
| 615TL         | WORKMASTER™ 45,<br>WORKMASTER™ 55               |
| 625TL         | WORKMASTER™ 65,<br>WORKMASTER™ 75, TT60A, TT75A |



Learn more at [www.newholland.com/na](http://www.newholland.com/na)



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2012 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

# COMPACT LOADER SERIES

## MODELS 235TLA, 240TLA, 250TLA

| LOADER MODEL   | 235TLA                 | 240TLA                 | 250TLA                 |
|--|------------------------|------------------------|------------------------|
| TRACTOR FAMILY/SERIES                                      | Boomer™ 20, Boomer™ 25 | Boomer™ 30, Boomer™ 35 | Boomer™ 40, Boomer™ 50 |
| <b>LOADER TYPE - NON-SELF LEVELING</b>                     |                        |                        |                        |
| Axle type  | Standard               | Standard               | Standard               |
| Max. lift height, ft. (mm)                                 | 6.7 (2050)             | 8.1 (2480)             | 8.9 (2712)             |
| Dump clearance, ft. (mm)                                   | 5.2 (1580)             | 6.0 (1835)             | 6.6 (2007)             |
| Lift capacity @ 1500 mm from bucket pivot point, lb. (kg)  | 1,034 (470)            | 1,370 (621)            | 1,940 (880)            |
| Breakout force @ 1500 mm from bucket pivot point, lb. (kg) | 1,672 (760)            | 2,925 (1327)           | 3,470 (1574)           |
| Reach @ maximum lift, in. (mm)                             | 25.2 (640)             | 34.0 (864)             | 32.0 (813)             |
| Bucket rollback angle, degrees                             | 29                     | 30.4                   | 30.3                   |
| Bucket dump angle, degrees                                 | 51                     | 41.3                   | 51.4                   |



Learn more at [www.newholland.com/na](http://www.newholland.com/na)



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2012 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.



# COMPACT LOADER SERIES

## MODEL 110TL, 250TL

| LOADER MODEL   | 110TL        | 250TL        |
|--|--------------|--------------|
| TRACTOR FAMILY/SERIES                                      | T1510, T1520 | T1530        |
| <b>LOADER TYPE - NON-SELF LEVELING</b>                     |              |              |
| Axle type  | Standard     | Standard     |
| Max. lift height, ft. (mm)                                 | 8.4 (2553)   | 8.8 (2682)   |
| Dump clearance, ft. (mm)                                   | 7 (2134)     | 6.8 (2073)   |
| Digging depth, in. (mm)                                    | 4 (102)      | 6.5 (165)    |
| Lift capacity @ 1500 mm from bucket pivot point, lb. (kg)  | 875 (397)    | 1,540 (699)  |
| Breakout force @ 1500 mm from bucket pivot point, lb. (kg) | 1602 (727)   | 2,640 (1197) |
| Reach @ maximum lift, in. (mm)                             | 12.75 (324)  | 33 (838)     |
| Bucket rollback angle, degrees                             | 20           | 30           |
| Bucket dump angle, degrees                                 | 38           | 58           |



Learn more at [www.newholland.com/na](http://www.newholland.com/na)



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2012 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

# UTILITY LOADER SERIES

## MODEL 615TL, 625TL

| LOADER MODEL   | 615TL                        | 625TL  |
|--|------------------------------|--|
| TRACTOR FAMILY/SERIES                                      | Workmaster 45, Workmaster 55 | Workmaster 65, Workmaster 75<br>TT60A, TT75A |
| <b>LOADER TYPE - NON-SELF LEVELING</b>                     |                              |  |
| Axle type  | Standard                     | Standard                                     |
| Max. lift height, ft. (mm)                                 | 9.25 (2819)                  | 10.5 (3200)                                  |
| Dump clearance, ft. (mm)                                   | 6.8 (2073)                   | 8.3 (2530)                                   |
| Digging depth, in. (mm)                                    | 4 (102)                      | 4 (102)                                      |
| Lift capacity @ 1500 mm from bucket pivot point, lb. (kg)  | 3461 (1570)                  | 3,450 (1565)                                 |
| Breakout force @ 1500 mm from bucket pivot point, lb. (kg) | 1950 (885)                   | 4,670 (2119)                                 |
| Reach @ maximum lift, in. (mm)                             | 43 (1092)                    | 31 (787)                                     |
| Bucket rollback angle, degrees                             | 23                           | 24   |
| Bucket dump angle, degrees                                 | 43                           | 37   |



Learn more at [www.newholland.com/na](http://www.newholland.com/na)



Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2012 CNH America LLC. All rights reserved. New Holland and CNH Capital are registered trademarks of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.