

# Fransgård GT - Levellers



**GT-210**  
**GT-250**  
**GT-250S**  
**GT-250HY**  
**GT-275HY**  
**GT-250FL**  
**GT-300FL**

Leveller for smoothing and clearing gravel roads, forest roads, soil, snow, etc.

Several mechanical and hydraulic versions available for front- or back-mounting.

Robust, high-quality, and user-friendly levellers with many possible settings.

Wide range of accessories.

**Fransgård**





Two linkage possibilities for lift arms and top link on all GT models. Ideal adaptation to the terrain via the oblong hole in the top link.



The GT-210/250 and GT-250S are available as a front model with a short boom so it does not sit as far ahead of the tractor. The front model can also be reversed and used for pulling behind the tractor.



The GT-FL can be mounted on a front hydraulic hitch or a front-end loader. This scraper is perfect for clearing squares, yards or stables. The centermounted scraper creates even pressure on the loader.



Two robust cylinders are standard and rotate the blade 23° to each side. Overload protection is provided by the three large springs, and the scraper automatically tilts into place after release. All revolving links can be lubricated.



All GT models are prepared for mounting stabilizer wheels, which are easy to adjust individually, without tools, at 25 mm intervals.



The GT-HY scraper comes standard with a hydraulic cylinder for scraper adjustments. The scraper can be turned up to 230°.



Manual, tool-free, right or left sideways displacement of the scraper. (Not available on model GT-FL)



The scraper is adjustable 360° in 10 positions. Tool-free manual adjustment. (Not GT-HY and GT-FL)



All GT models come standard with the ends prepared for mounting of an end-plate or snow wing.



On the GT-250S the scraper's vertical angle can be adjusted offering three blade pitch positions, providing a more aggressive clearing angle. Tool-free manual adjustment.



Technical data	GT-210/front	GT-250/front	GT-250S/front	GT-250HY/275HY	GT-250FL/300FL
Working width	2.10 m	2.50 m	2.50 m	2.50 / 2.75 m	2.50 / 3.00 m
Scraper height	60 cm	60 cm	60 cm	60 cm	60 cm
Reversible wear strip	Standard	Standard	Standard	Standard	Standard
Gauge wheels	Optional	Optional	Optional	Optional	Optional
Offset adjustment	50 / 20 cm	50 / 20 cm	50 / 20 cm	55 / 55 cm	No / No
Rotating scraper blade	360°	360°	360°	230°	23° (35°)
Vertical adjustment	1 pos.	1 pos.	3 pos.	1 pos.	1 pos.
Hydr. adjustment	Optional / No	Possible / No	Possible / No	Standard	Standard
Three-point suspension	Cat. I/II	Cat. I/II	Cat. I/II	Cat. I/II	Cat. II.
Front-end loader mount.	No	No	No	No	EURO or SMS
Hydr. outlet	-	-	-	1 double	1 double
Net weight	360 / 340 kg	385 / 365 kg	425 / 405 kg	450 / 475 kg	450 / 490 kg

## Accessories



Large Gauge wheels with balloon tyres. 15 x 6.00.



End-plate to restrain the material. Can be mounted on both sides.



Snow wing that scrapes the edge diagonally so the snow does not fall down behind the scraper.



Rubber wear-strip for clearing hard surfaces and areas with paving stones.



Plain/serrated wear - resistant steel is standard. Plain/plain or serrated/serrated can be mounted as required.



Telescopic cylinder increases the angle of GT-FL scrapers up to 35°.

## Fransgård also offers



Chain mower FKR-150



Snow blower V-230



Spreader SPR-250

Importer

Dealer

Manufacturer:

Fransgård Maskinfabrik A/S

Fredbjergvej 132

DK-9640 Farsø

Tlf. +45 98 63 21 22

www.fransgard.dk