

## Rotary Cutter - Flex-Wing

| MODEL                        | 1530                       |                            |
|------------------------------|----------------------------|----------------------------|
| Width, working               | 186 in (4.7 m)             |                            |
| Width, overall               | 194 in (4.9 m)             |                            |
| Width, transport             | 98 in (2.5 m)              |                            |
| Height, transport            | 92 in (2.3 m)              |                            |
| Working range                | +/- 25°                    |                            |
| Cutting height               | 2 to 15 in (51 to 381 mm)  |                            |
| Weight                       | 5900 lb (2676 kg)          |                            |
| Tongue weight                | 2100 lb (953 kg)           |                            |
| Tractor hp requirement, min. | 65 hp                      |                            |
| Gearbox hp: splitter / wings | 250 hp / 190 hp            |                            |
| Gearbox speed                | 540 RPM                    | 1000 RPM                   |
| Wing blade tip speed         | 16,481 ft/min (5023 m/min) | 16,737 ft/min (5101 m/min) |
| Center blade tip speed       | 16,197 ft/min (4937 m/min) | 15,802 ft/min (4816 m/min) |
| Blade overlap                | 7 in (177 mm)              |                            |
| Blade                        | 0.5 x 4, Uplift            |                            |
| Deck material thickness      | 0.179 in (7 Ga) (4.5 mm)   |                            |
| Side skirt thickness         | 0.25 in (6.4 mm)           |                            |
| Hitch                        | Category 2 clevis          |                            |

| STANDARD EQUIPMENT   | OPTIONAL EQUIPMENT |
|----------------------|--------------------|
| Single chain guard   | Double axle        |
| Deck protection ring |                    |
| Stump jumper         |                    |