

RECOMMENDED HEADER SETTINGS FOR DIRECT CUTTING

Stubble Height (in.)	Crop Condition	OPERATING VARIABLES											
		Divider Rods	Draper Speed (Note 7)	Header Angle (Note 1 & 2)	Knife Speed (Note 2)	Reel Cam Setting	Reel Speed % (Note 3)	Reel Position	Skid Shoe Position (Note 4)	Stabilizer Wheel (Note 4 & 5)	Upper Cross Auger		
CEREALS													
< 4	Light	Off	8	B - C	600-650	3	10 - 15	6 or 7	Up or Center	Storage	Not Required		
	Normal	On	7		550-600	2	10				Recommended		
	Heavy	Off			525-600	3 or 4	5 - 10				4 or 5	Not Required	
4-8	Light	Off	8	B - C	600-650	4	10 - 15	6 or 7	Center or Down	Note 5	Not Required		
	Normal	On	7	A	550-600	2	10				Recommended		
	Heavy	Off		D	525-600	3 or 4	5 - 10				4 or 5	Not Required	
10+	Light	Off	8	A	600-650	4	10 - 15	6 or 7	N/A	Note 5	Not Required		
	Normal	On	7		550-600	2	10						
	Heavy	Off		B - C	525-600	3 or 4	5 - 10					4 or 5	
CANOLA													
4-8	Light	On	7	A	600-650	2	5 - 10	6 or 7	Down	Note 5	Recommended		
	Normal		8	B - C	550-600	1	10		Center or Down				
	Heavy		7	D	525-600	2	5 - 10		3 or 4			Down	
	Lodged											Center or Down	
10+	Light	On	7	A	600-650	2	5 - 10	6 or 7	N/A	Note 5	Recommended		
	Normal		8	B - C	550-600	1 or 2	10						
	Heavy		7	D	525-600	2 or 3	5 - 10					3 or 4	
	Lodged												
CALIFORNIA RICE													
< 4	Light	Rice Divider Rod (Note 6)	4	D	600-650	2	10 - 15	6 or 7	Up or Center	Storage	Not Required		
	Normal			B - C	550-600		10						
	Heavy			D	525-600		5 - 10					4 or 5	
	Lodged												
4-8	Light	Rice Divider Rod (Note 6)	4	D	600-650	3	10 - 15	6 or 7	Center or Down	Note 5	Not Required		
	Normal			B - C	550-600		10						
	Heavy			D	525-600		5 - 10						
	Lodged												
10+	Light	Rice Divider Rod (Note 6)	4	A	600-650	3	10 - 15	6 or 7	N/A	Note 5	Not Required		
	Normal			B - C	550-600		10						
	Heavy			D	525-600		5 - 10						
	Lodged												
DELTA RICE													
2 - 6	Light	Off	6	D	600-650	2 or 3	10 - 15	6 or 7	Center or Down	Note 5	Not Required		
	Normal			B - C	550-600		10						
	Heavy			D	525-600		3 or 4					5 - 10	4 or 5
	Lodged												
8+	Light	Off	6	A	600-650	2 or 3	10 - 15	6 or 7	N/A	Note 5	Not Required		
	Normal			B - C	550-600		10						
	Heavy			D	525-600		3 or 4					5 - 10	4 or 5
	Lodged												
SOYBEANS													
	Light	On	8	D	600-650	2	5 - 10	6 or 7	Up or Center	Storage	Not Required		
	Normal		7	B - C	550-600		10						
	Heavy			D	525-600		5 - 10						
	Lodged												
FLAX													
	Light	On	8	B - C	600-650	2	5 - 10	6 or 7	Center or Down	Note 5	Not Required		
	Normal		7	A			10						
	Heavy			B - C									
	Lodged			D			5 - 10		Down				
PEAS													
	Light	On	7	B - C	600-650	2	5 - 10	6 or 7	Up or Center	Storage	Recommended		
	Normal				550-600		10					4 or 5	
	Heavy				D		525-600					5 - 10	
	Lodged												
LENTILS													
	Light	On	8	B - C	600-650	2	5 - 10	6 or 7	Up or Center	Storage	Not Required		
	Normal				7		550-600					10	
	Heavy						D					525-600	5 - 10
	Lodged												



Visit [YouTube.com/MacDonVideos](https://www.youtube.com/MacDonVideos) and watch our **MacDon FD75 Flexdraper Setup Playlist** or Scan Here

NOTES

1. Set header angle as shallow as possible (setting A) with center-link and skid shoes while maintaining cutting height.
2. Minimum knife drive pulley rpm. Applicable only to single-knife headers.
3. Percentage above ground speed.
4. Cutting height is controlled with a combination of skid shoes and header angle.
5. Stabilizer wheels are used to limit the side to side movement when cutting off the ground in rolling terrain, and to minimize bouncing.
6. Available through your Dealer. Rice Divider Rod not required on both ends of header.
7. Setting on CA25 draper control.