

DIMENSIONS	851	1051
Width - overall		
Radial tires	14' 2"	14' 2"
Length - overall		
Length	28' 4"	30' 4"
Height		
Short side height	11' 1"	11' 7"
High side height	12' 1"	12' 7"
SPECIFICATIONS		
Capacity		
Heaped Capacity	850 bu. ¹	1,050 bu. ¹
Weight		
Radial tires (empty)	14,640 lbs.	15,100 lbs.
Tracks by Camso (empty)	N/A	23,000 lbs.
Hitch (empty)	2,500 lbs.	2,500 lbs.
Hitch (loaded) ¹	5,000 lbs.	5,000 lbs.
Auger		
Diameter	20"	20"
Reach	7' 3"	7' 3"
Height	13' 4"	13' 4"
Other		
Unload - bushel per minute	475 bu/min ²	475 bu/min ²
Adjustable discharge spout	35°	35°
Hydraulic requirements	3 SCVs	3 SCVs
PTO	1 ¾" - 1000 rpm	1 ¾" - 1000 rpm

¹ Cart hitch weight based on #2 corn at 15% moisture (56lb test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors.

² Bushels per minute may vary with moisture content of grain and/or PTO rpm.